

2009 IPHC Stock Assessment Survey

Area 3B

Station	Date Fishe	North Latitude	West Longitude	Depth (F)	Skates Set ¹	Legal Halibut		Sublegal Halibut		Bycatch (numbers) ³		
						Lbs. ²	#'s	Lbs. ²	#'s	Sablefish	P. Cod	Rockfish
5001	8/10	55° 59.63'	-153° 36.36'	52	7.1	1,407	79	1,067	144	0	0	20
5002	8/10	56° 00.52'	-153° 54.25'	56	7.0	1,349	74	607	91	0	20	0
5003	8/9	56° 00.33'	-154° 13.74'	57	7.0	1,664	96	353	44	0	0	60
5004	8/9	56° 00.42'	-154° 29.42'	228	7.0	26	2	0	0	100	0	55
5005	8/7	56° 00.26'	-154° 48.78'	111	7.0	320	21	118	14	165	5	0
5006	8/7	56° 00.05'	-155° 05.48'	33	7.0	162	13	861	114	0	275	0
5007	8/11	56° 10.95'	-153° 36.65'	71	7.0	697	40	216	26	0	105	0
5008	8/10	56° 09.50'	-153° 52.80'	126	7.0	995	60	37	4	10	10	10
5009	8/8	56° 10.29'	-154° 11.26'	63	7.0	434	32	487	78	0	130	0
5010	8/9	56° 10.18'	-154° 28.57'	50	7.1	1,555	89	901	117	0	61	10
5011	8/7	56° 09.61'	-154° 46.78'	46	7.0	528	34	507	64	0	180	0
5013	8/1	56° 10.43'	-155° 23.05'	20	7.0	1,197	69	1,025	138	0	65	0
5014	8/1	56° 10.23'	-155° 40.62'	32	7.0	192	14	640	101	0	170	0
5015	8/11	56° 19.43'	-153° 51.09'	48	7.1	1,207	46	589	78	0	20	0
5016	8/8	56° 19.55'	-154° 11.05'	50	7.0	347	19	313	43	0	155	0
5017	8/8	56° 19.38'	-154° 27.63'	37	7.0	701	34	304	37	0	110	0
5018	8/2	56° 20.17'	-155° 21.88'	24	7.0	284	20	648	88	0	220	0
5019	8/1	56° 19.69'	-155° 39.99'	38	7.0	312	12	318	45	0	210	0
5020	8/2	56° 29.19'	-155° 21.37'	27	7.0	566	36	1,179	169	0	35	0
5021	8/2	56° 29.88'	-155° 39.10'	59	7.0	142	9	473	70	0	270	0
5022	8/6	56° 40.05'	-155° 01.73'	21	7.0	1,693	78	287	38	0	0	0
5023	8/6	56° 40.24'	-155° 19.79'	52	7.0	760	45	407	53	0	160	0
5024	7/31	56° 39.95'	-155° 38.87'	131	7.0	729	41	87	10	60	30	0
5025	7/31	56° 40.15'	-155° 56.24'	159	7.0	603	35	72	8	55	65	0
5026	8/5	56° 49.88'	-154° 23.82'	32	7.0	309	15	193	24	0	20	0
5027	8/5	56° 50.34'	-154° 41.42'	27	7.0	774	50	397	54	0	15	0
5028	8/6	56° 50.10'	-155° 00.54'	41	7.0	1,464	89	897	120	0	90	0
5029	7/24	56° 50.53'	-155° 18.89'	126	7.0	714	43	78	8	50	70	0
5030	7/23	56° 50.33'	-155° 37.17'	151	7.0	390	20	26	4	89	89	0
5031	7/31	56° 49.52'	-155° 55.34'	162	7.0	96	5	0	0	170	115	5
5032	8/5	56° 59.58'	-154° 40.77'	20	7.0	427	25	315	42	0	0	0
5033	7/24	56° 59.61'	-154° 59.80'	62	7.0	1,063	68	797	99	0	75	0
5034	7/24	56° 59.75'	-155° 17.04'	136	7.0	471	27	57	6	85	45	0
5035	7/23	56° 59.78'	-155° 36.23'	153	7.0	404	21	19	3	60	35	0
5036	7/23	57° 00.16'	-155° 53.66'	163	7.0	276	12	21	2	104	188	0
5037	7/25	57° 10.03'	-154° 40.77'	36	7.1	994	49	419	59	0	61	0
5038	7/25	57° 10.29'	-154° 56.63'	101	7.0	1,049	50	184	22	10	155	0
5039	7/30	57° 10.13'	-155° 15.49'	133	7.0	222	15	33	4	55	100	0
5040	7/30	57° 10.04'	-155° 34.70'	146	7.0	661	33	54	6	104	84	0
5041	7/22	57° 09.96'	-155° 53.47'	142	7.0	219	9	59	7	50	240	0
5042	7/26	57° 19.24'	-154° 55.13'	76	6.6	803	41	382	42	0	98	0
5043	7/30	57° 19.51'	-155° 14.75'	133	7.0	583	33	78	9	85	50	5
5044	7/20	57° 19.98'	-155° 34.47'	153	7.1	644	35	96	11	146	5	0
5045	7/22	57° 19.98'	-155° 51.89'	62	7.1	581	27	124	14	0	247	0
5046	7/22	57° 20.30'	-156° 10.64'	90	7.0	169	10	130	15	0	190	0
5047	7/20	57° 29.69'	-155° 14.04'	138	7.1	423	18	16	2	111	35	0
5048	7/20	57° 29.66'	-155° 32.55'	163	7.0	999	58	211	23	150	40	0
5096	6/28	54° 50.11'	-157° 33.05'	221	7.0	316	21	106	12	110	0	25
5097	7/12	54° 50.00'	-157° 50.00'	91	7.0	249	17	382	53	0	55	0
5098	6/28	55° 00.00'	-157° 14.97'	106	7.0	589	39	496	61	10	5	0

¹ Standard skate = 1,800' groundline with 16/0 circle hooks spaced every 18' on 24"-42" gangions.

² Weights are calculated from length-weight tables.

³ Bycatch numbers extrapolated from 20% subsample.

2009 IPHC Stock Assessment Survey

Area 3B

Station	Date Fishe	North Latitude	West Longitude	Depth (F)	Skates Set ¹	Legal Halibut		Sublegal Halibut		Bycatch (numbers) ³		
						Lbs. ²	#'s	Lbs. ²	#'s	Sablefish	P. Cod	Rockfish
5099	6/28	55° 00.05'	-157° 32.02'	53	7.0	2,323	143	409	56	0	130	10
5100	7/12	55° 00.00'	-157° 49.98'	45	7.0	2,071	106	636	79	0	125	5
5101	7/12	54° 59.99'	-158° 07.05'	71	7.0	314	18	482	75	0	45	0
5102	6/10	55° 10.02'	-156° 21.99'	288	6.8	0	0	0	0	116	0	0
5103	6/30	55° 10.17'	-156° 39.03'	285	7.0	32	2	10	1	203	0	0
5104	6/29	55° 10.02'	-156° 57.06'	85	7.0	414	31	374	47	0	223	0
5105	6/29	55° 10.01'	-157° 13.82'	61	6.8	829	51	750	110	0	78	0
5106	7/11	55° 10.00'	-157° 32.03'	46	7.0	1,830	88	1,106	151	0	5	0
5107	7/11	55° 09.98'	-157° 48.83'	43	7.0	1,100	55	919	132	0	15	0
5108	6/27	55° 10.04'	-158° 07.02'	56	7.0	1,163	59	643	94	0	10	0
5109	6/30	55° 20.00'	-156° 38.88'	64	7.0	1,126	68	1,337	186	0	75	0
5110	6/30	55° 19.98'	-156° 55.96'	50	7.0	428	25	502	82	0	203	0
5111	6/29	55° 19.99'	-157° 14.01'	49	6.8	643	34	581	88	0	155	0
5112	7/11	55° 19.99'	-157° 31.06'	48	7.1	261	17	821	128	0	81	0
5113	7/10	55° 19.98'	-157° 48.99'	44	7.1	284	13	1,023	176	0	5	0
5114	7/13	55° 20.02'	-158° 05.85'	59	7.0	405	25	648	92	0	25	0
5115	6/27	55° 19.93'	-158° 24.03'	80	6.9	795	48	488	64	5	92	0
5116	6/9	55° 29.77'	-156° 38.00'	97	6.8	2,678	167	618	77	19	39	0
5117	6/9	55° 30.00'	-156° 55.36'	48	6.7	2,044	112	1,076	133	0	101	5
5118	7/9	55° 29.96'	-157° 13.02'	47	7.0	1,274	65	1,490	200	0	10	0
5119	7/10	55° 29.99'	-157° 31.11'	52	6.9	570	27	369	54	0	162	0
5120	7/10	55° 29.99'	-157° 47.84'	53	6.9	252	14	702	104	0	39	0
5121	7/13	55° 30.00'	-158° 06.16'	71	7.0	551	36	795	104	0	30	0
5122	7/13	55° 29.99'	-158° 24.00'	80	7.0	637	42	483	59	0	114	0
5123	7/9	55° 40.00'	-156° 55.09'	49	7.0	481	25	909	133	0	35	0
5124	7/9	55° 39.99'	-157° 12.84'	47	7.0	429	17	603	100	0	35	0
5125	7/8	55° 39.94'	-157° 29.99'	55	7.0	578	42	1,221	173	0	59	0
5126	7/18	55° 40.01'	-157° 48.05'	73	7.0	485	33	613	76	0	188	0
5127	7/18	55° 39.99'	-158° 06.01'	69	7.0	661	42	555	71	5	100	0
5128	7/19	55° 40.00'	-158° 23.05'	71	7.0	1,019	71	914	116	0	80	0
5129	7/19	55° 40.01'	-158° 40.88'	48	7.0	344	19	1,169	165	0	5	0
5130	7/8	55° 49.98'	-157° 11.79'	55	7.0	375	27	928	131	0	95	0
5131	7/8	55° 49.99'	-157° 30.01'	57	7.0	444	30	732	106	0	104	0
5132	7/17	55° 49.99'	-157° 48.28'	66	7.0	557	38	835	109	0	135	0
5133	7/18	55° 50.09'	-158° 05.00'	45	7.0	586	34	1,135	168	0	10	0
5134	7/19	55° 49.89'	-158° 22.98'	59	7.0	729	35	526	73	0	175	0
5135	7/7	55° 59.94'	-157° 29.01'	59	7.0	847	41	352	49	0	203	0
5136	7/17	56° 00.00'	-157° 46.89'	67	7.0	1,211	81	623	76	0	174	0
5137	7/17	55° 59.98'	-158° 04.92'	45	7.0	1,470	66	635	85	0	105	0
5138	7/16	56° 10.02'	-157° 46.98'	86	6.9	868	36	178	23	0	348	0
5139	7/16	56° 10.00'	-158° 04.86'	36	7.2	1,066	51	306	42	0	71	0
5140	7/16	56° 19.98'	-158° 03.93'	41	6.9	691	29	149	19	0	25	0
5141	6/16	54° 29.96'	-159° 01.00'	143	7.1	103	9	208	28	116	15	15
5142	6/16	54° 29.98'	-159° 17.29'	79	7.0	247	18	229	31	0	54	0
5143	6/18	54° 29.88'	-159° 34.00'	63	7.0	1,365	98	700	89	0	170	10
5144	6/19	54° 30.01'	-159° 51.15'	65	7.0	176	12	334	52	0	30	0
5145	6/19	54° 30.00'	-160° 09.23'	66	7.0	638	44	362	50	0	95	0
5146	6/2	54° 39.97'	-158° 25.17'	114	7.0	911	69	1,150	138	55	100	0
5147	6/15	54° 39.81'	-158° 41.98'	58	7.0	1,267	85	907	117	0	175	10
5148	6/15	54° 40.00'	-159° 00.14'	51	7.0	1,332	82	464	57	0	129	5

¹ Standard skate = 1,800' groundline with 16/0 circle hooks spaced every 18' on 24"-42" gangions.

² Weights are calculated from length-weight tables.

³ Bycatch numbers extrapolated from 20% subsample.

2009 IPHC Stock Assessment Survey

Area 3B

Station	Date Fishe	North Latitude	West Longitude	Depth (F)	Skates Set ¹	Legal Halibut		Sublegal Halibut		Bycatch (numbers) ³		
						Lbs. ²	#'s	Lbs. ²	#'s	Sablefish	P. Cod	Rockfish
5149	6/16	54° 39.92'	-159° 17.09'	41	7.0	957	44	558	80	0	130	0
5150	6/18	54° 40.02'	-159° 34.08'	34	7.1	488	20	329	41	0	268	0
5151	6/18	54° 40.13'	-159° 52.00'	41	7.0	1,594	72	493	68	0	230	0
5152	6/17	54° 40.12'	-160° 09.00'	49	7.0	1,168	71	739	96	0	105	0
5153	6/2	54° 50.01'	-158° 07.00'	55	7.1	1,179	83	1,519	223	5	51	0
5154	6/2	54° 49.90'	-158° 25.02'	110	7.0	1,161	74	549	69	79	59	0
5155	6/15	54° 50.02'	-158° 42.02'	55	7.0	933	46	875	133	0	125	0
5156	6/14	54° 49.91'	-159° 00.00'	40	7.0	262	17	664	117	0	130	0
5157	6/17	54° 49.98'	-159° 52.39'	31	7.0	387	16	152	24	0	257	0
5158	6/17	54° 50.00'	-160° 09.08'	38	7.0	663	31	368	56	0	189	0
5159	6/20	54° 50.01'	-160° 25.96'	46	7.0	195	12	138	20	0	330	0
5160	6/3	55° 00.00'	-158° 25.71'	114	6.9	834	52	316	36	136	39	0
5161	6/3	54° 59.99'	-158° 41.97'	70	7.0	918	55	888	134	0	114	5
5162	6/14	54° 59.98'	-158° 58.82'	46	7.0	273	16	511	86	0	205	0
5163	6/14	54° 59.51'	-159° 16.77'	23	7.0	589	24	87	10	0	110	0
5164	6/20	54° 59.97'	-160° 27.04'	61	7.0	862	59	932	128	0	125	0
5165	6/20	55° 00.11'	-160° 44.00'	47	7.0	690	42	1,393	210	0	25	0
5166	6/3	55° 09.93'	-158° 23.99'	100	7.1	816	54	401	52	15	5	0
5167	6/13	55° 10.00'	-158° 41.70'	112	7.0	1,562	93	324	37	30	55	0
5168	6/13	55° 09.72'	-158° 58.98'	72	7.0	928	56	777	103	0	109	0
5169	6/5	55° 10.09'	-159° 17.01'	38	7.0	496	26	206	28	0	388	0
5170	6/6	55° 20.00'	-158° 42.02'	103	7.0	705	41	130	17	10	100	0
5171	6/13	55° 19.88'	-158° 58.98'	103	7.0	779	43	274	33	0	30	0
5172	6/5	55° 20.11'	-159° 17.02'	96	7.0	2,575	149	533	60	0	86	0
5173	6/5	55° 19.85'	-159° 34.22'	76	7.0	1,043	59	351	46	0	207	0
5174	6/9	55° 19.91'	-159° 52.03'	46	7.1	560	29	423	57	0	263	0
5175	6/6	55° 29.97'	-158° 41.34'	88	7.0	1,192	70	324	40	0	59	0
5176	6/6	55° 29.99'	-158° 59.20'	60	7.0	320	21	942	150	0	119	0
5177	6/8	55° 29.66'	-159° 16.98'	69	7.0	536	32	564	79	0	208	0
5178	6/8	55° 29.98'	-159° 34.23'	92	7.0	1,161	58	198	23	0	115	0
5179	6/9	55° 29.91'	-159° 51.98'	92	7.0	726	40	302	39	0	201	0
5181	6/7	55° 40.01'	-158° 59.12'	83	7.0	883	48	323	39	0	283	0
5182	6/8	55° 39.90'	-159° 16.96'	57	7.0	392	25	297	41	0	194	0
5183	6/9	55° 40.00'	-159° 51.89'	71	7.0	558	31	126	17	0	277	0
5184	6/7	55° 50.13'	-158° 59.00'	68	7.1	1,061	50	302	38	0	222	0
5185	6/7	55° 49.98'	-159° 16.91'	34	7.0	312	18	100	14	0	290	0
5186	8/8	54° 00.01'	-163° 14.89'	46	7.0	493	35	698	104	0	198	15
5187	8/8	54° 00.00'	-163° 31.69'	56	7.0	50	4	274	47	0	150	0
5188	8/8	54° 00.02'	-163° 48.91'	52	7.0	35	2	154	30	0	305	0
5189	8/10	54° 09.99'	-161° 33.66'	77	7.0	207	16	585	91	25	95	0
5190	8/10	54° 09.77'	-161° 50.99'	45	6.2	1,618	117	858	102	0	151	27
5191	8/9	54° 10.05'	-162° 08.07'	46	7.1	1,720	107	746	91	0	162	20
5192	8/9	54° 10.00'	-162° 25.05'	94	7.0	165	12	312	42	65	35	30
5193	6/28	54° 09.52'	-163° 49.98'	48	7.0	241	17	303	44	0	170	0
5194	6/19	54° 20.00'	-160° 07.90'	179	7.0	68	6	99	12	74	0	25
5195	8/11	54° 19.99'	-160° 26.27'	69	7.0	716	49	530	81	0	170	0
5196	8/19	54° 20.00'	-160° 42.98'	58	7.0	1,139	74	352	46	0	305	20
5197	8/19	54° 20.01'	-161° 00.07'	69	7.0	167	13	623	99	0	195	0
5198	8/18	54° 19.97'	-161° 17.12'	59	7.0	1,392	93	503	61	0	240	10
5199	8/18	54° 20.00'	-161° 34.00'	79	7.0	138	11	578	94	30	64	0

¹ Standard skate = 1,800' groundline with 16/0 circle hooks spaced every 18' on 24"-42" gangions.

² Weights are calculated from length-weight tables.

³ Bycatch numbers extrapolated from 20% subsample.

2009 IPHC Stock Assessment Survey

Area 3B

Station	Date Fishe	North Latitude	West Longitude	Depth (F)	Skates Set ¹	Legal Halibut		Sublegal Halibut		Bycatch (numbers) ³		
						Lbs. ²	#'s	Lbs. ²	#'s	Sablefish	P. Cod	Rockfish
5200	8/10	54° 20.00'	-161° 50.69'	41	7.0	1,256	78	887	122	0	135	5
5201	8/9	54° 19.98'	-162° 09.00'	31	7.0	1,698	106	1,171	148	0	50	0
5202	6/26	54° 20.04'	-163° 16.99'	27	7.0	875	46	163	21	0	129	0
5203	6/26	54° 19.98'	-163° 34.11'	61	7.0	361	24	434	57	0	295	0
5204	6/28	54° 19.98'	-163° 51.02'	62	7.0	695	48	970	134	0	119	0
5205	6/28	54° 19.87'	-164° 08.98'	53	7.0	215	14	436	60	0	265	0
5206	8/11	54° 29.99'	-160° 26.41'	81	7.0	660	54	931	122	5	115	0
5207	8/19	54° 29.98'	-160° 42.98'	76	7.0	164	11	123	16	5	85	0
5208	8/20	54° 29.98'	-161° 00.22'	71	7.0	115	7	406	61	55	110	0
5209	8/20	54° 29.98'	-161° 18.29'	64	7.0	230	14	445	75	0	115	0
5210	8/18	54° 29.84'	-161° 35.00'	36	7.0	1,210	79	1,178	171	0	105	0
5211	8/17	54° 30.02'	-161° 51.96'	79	7.0	486	32	347	44	0	30	0
5212	8/17	54° 30.01'	-162° 08.79'	79	7.0	899	59	514	66	0	75	0
5213	8/17	54° 30.01'	-162° 26.11'	80	7.0	1,449	80	589	74	0	135	0
5214	6/26	54° 30.09'	-163° 18.01'	41	7.0	478	30	653	99	0	178	0
5215	6/27	54° 29.88'	-163° 35.00'	55	7.0	223	13	505	82	0	40	0
5216	6/27	54° 30.00'	-163° 53.24'	52	7.0	505	39	1,239	189	0	30	0
5217	6/27	54° 29.99'	-164° 10.12'	54	7.0	384	28	1,086	171	0	65	0
5218	8/11	54° 40.00'	-160° 26.04'	56	7.0	1,168	69	1,106	160	0	180	0
5219	8/21	54° 39.98'	-160° 42.94'	53	7.0	1,297	83	481	64	0	278	0
5220	8/20	54° 40.10'	-161° 00.50'	49	7.0	1,476	88	1,201	169	0	95	0
5221	8/16	54° 40.01'	-161° 18.27'	77	7.0	250	17	773	106	0	50	0
5222	6/21	54° 39.98'	-161° 35.12'	36	7.0	996	43	498	72	0	135	5
5223	6/21	54° 40.00'	-161° 53.05'	43	7.0	542	21	336	50	0	280	5
5224	6/25	54° 39.98'	-162° 43.99'	47	7.0	856	57	1,014	140	5	85	0
5225	8/21	54° 49.98'	-160° 44.14'	56	7.0	138	10	956	132	0	165	0
5226	8/16	54° 49.92'	-161° 01.00'	57	7.1	649	43	827	111	0	5	0
5227	8/16	54° 49.94'	-161° 17.98'	55	7.0	164	10	407	62	0	0	0
5228	6/21	54° 49.91'	-161° 36.00'	43	7.0	1,520	67	691	100	0	94	0
5229	6/25	54° 50.00'	-162° 44.94'	27	7.0	896	52	568	84	0	75	0
5230	6/25	54° 49.98'	-163° 03.15'	46	7.0	599	39	599	78	0	150	0
5231	8/15	55° 00.00'	-161° 01.07'	55	7.0	1,036	58	700	92	0	94	0
5232	8/15	55° 00.01'	-161° 19.21'	49	7.0	973	54	841	118	0	40	0
5233	8/15	55° 09.93'	-161° 01.98'	74	7.0	422	27	249	31	0	270	0
5234	6/10	55° 20.00'	-156° 03.14'	151	6.9	2,699	162	379	45	49	0	29
5235	6/10	55° 19.98'	-156° 21.01'	96	6.7	1,007	62	427	53	5	58	0
5236	5/30	55° 29.95'	-155° 45.00'	121	6.7	1,393	93	740	93	5	0	0
5237	5/30	55° 29.96'	-156° 02.98'	110	6.7	787	48	480	65	58	43	0
5238	7/1	55° 30.00'	-156° 19.91'	118	7.0	1,214	74	249	29	70	85	0
5239	5/29	55° 40.17'	-155° 26.01'	101	6.8	1,137	74	498	70	0	19	0
5240	5/30	55° 39.82'	-155° 43.99'	69	6.8	897	55	753	105	0	87	0
5241	7/1	55° 40.01'	-156° 01.67'	126	6.7	987	59	217	26	62	29	0
5242	7/1	55° 40.00'	-156° 18.80'	139	7.0	1,051	52	75	9	74	40	0
5243	6/9	55° 39.88'	-156° 37.02'	131	6.7	841	49	213	26	67	10	0
5244	5/29	55° 50.00'	-155° 07.15'	65	6.9	777	50	670	93	0	44	0
5245	5/29	55° 50.01'	-155° 24.15'	30	6.7	422	26	527	78	0	182	0
5246	5/31	55° 50.01'	-156° 01.16'	64	6.7	1,370	76	605	85	0	29	0
5247	6/3	55° 50.02'	-156° 19.09'	132	6.9	822	45	146	19	119	5	5
5248	6/8	55° 50.00'	-156° 36.36'	122	6.7	2,231	126	398	52	29	10	0
5249	6/8	55° 49.88'	-156° 54.00'	75	6.9	1,328	84	756	98	0	103	0

¹ Standard skate = 1,800' groundline with 16/0 circle hooks spaced every 18' on 24"-42" gangions.

² Weights are calculated from length-weight tables.

³ Bycatch numbers extrapolated from 20% subsample.

2009 IPHC Stock Assessment Survey

Area 3B

Station	Date Fishe	North Latitude	West Longitude	Depth (F)	Skates Set ¹	Legal Halibut		Sublegal Halibut		Bycatch (numbers) ³			
						Lbs. ²	#'s	Lbs. ²	#'s	Sablefish	P. Cod	Rockfish	
5250	6/2	55° 59.87'	-155° 42.02'	26	6.9	1,013	73	757	96	0	191	0	
5251	6/2	56° 00.05'	-155° 59.96'	42	6.8	675	45	1,095	161	0	49	0	
5252	6/3	56° 00.00'	-156° 18.40'	116	7.0	1,274	69	128	14	69	149	0	
5253	6/8	55° 59.76'	-156° 34.58'	108	6.8	1,293	72	330	43	5	68	0	
5254	7/7	55° 59.99'	-157° 11.00'	63	7.0	272	18	286	39	0	94	0	
5255	6/2	56° 09.97'	-155° 59.02'	119	6.9	898	54	728	89	64	113	0	
5256	6/7	56° 10.14'	-156° 16.99'	127	6.8	1,185	61	132	16	44	141	0	
5257	6/19	56° 09.99'	-156° 35.02'	102	7.0	346	21	179	29	0	188	0	
5258	6/20	56° 09.94'	-156° 52.97'	45	7.0	294	8	144	21	0	225	0	
5259	6/20	56° 09.99'	-157° 10.84'	54	7.0	895	32	242	35	0	205	0	
5260	7/7	56° 09.99'	-157° 29.03'	84	7.0	999	61	371	43	0	185	0	
5261	6/7	56° 19.97'	-155° 58.00'	114	6.7	1,139	70	394	48	62	5	0	
5262	6/7	56° 19.71'	-156° 16.00'	154	6.8	793	43	72	10	87	39	0	
5263	6/19	56° 20.05'	-156° 33.97'	102	7.1	1,759	92	169	21	15	152	0	
5264	6/19	56° 20.02'	-156° 51.72'	63	7.1	997	37	590	88	0	145	0	
5265	6/20	56° 20.02'	-157° 09.97'	95	6.9	892	44	90	11	0	265	0	
5266	6/21	56° 20.01'	-157° 28.02'	35	6.9	1,109	55	711	99	0	83	0	
5267	6/21	56° 20.00'	-157° 45.65'	29	7.2	1,799	85	500	65	0	117	0	
5268	6/6	56° 30.00'	-155° 57.14'	135	7.0	519	30	166	21	104	40	0	
5269	6/6	56° 30.00'	-156° 14.95'	145	7.0	1,143	54	79	10	185	35	0	
5270	6/18	56° 29.99'	-156° 33.25'	105	7.1	653	39	283	35	15	131	0	
5271	6/18	56° 30.00'	-156° 51.05'	56	7.0	475	25	530	76	0	161	0	
5272	6/21	56° 29.91'	-157° 28.02'	83	7.0	922	43	180	24	0	213	0	
5273	6/6	56° 40.00'	-156° 14.01'	116	7.0	1,264	63	238	27	89	158	0	
5274	6/18	56° 39.95'	-156° 32.01'	85	7.0	455	26	226	31	0	295	0	
5275	6/17	56° 40.00'	-156° 51.16'	58	7.0	475	29	425	63	0	115	0	
5276	6/17	56° 40.02'	-157° 08.96'	65	7.2	604	35	338	44	0	46	0	
5277	6/16	56° 50.00'	-156° 13.16'	106	7.2	750	36	225	30	0	111	0	
5278	6/16	56° 50.01'	-156° 31.87'	62	7.1	568	30	157	23	0	242	0	
5279	6/17	56° 50.01'	-156° 49.98'	56	7.0	720	37	257	32	0	215	0	
5280	6/16	57° 00.11'	-156° 12.94'	86	7.0	342	19	190	28	0	150	0	
231 Total Effective 3B Stations						Totals	181,946	10,482	114,758	15,832	4,117	25,961	452

¹ Standard skate =1,800' groundline with 16/0 circle hooks spaced every 18' on 24"-42" gangions.

² Weights are calculated from length-weight tables.

³ Bycatch numbers extrapolated from 20% subsample.