

2017 IPHC Fishery-Independent Setline Survey

Regulatory Area 3B

Station	Date Fished	North Latitude	West Longitude	Depth (F)	Skates ¹	O32 Halibut		U32 Halibut Bycatch (numbers) ³				
						Lbs. ²	#'s	Lbs. ²	#'s	Sablefish	P. Cod	Rockfish
5001	6/17	56° 00.41'	-153° 35.86'	50	5.0	925	53	590	72	0	0	5
5002	6/18	56° 00.04'	-153° 53.50'	65	4.9	125	7	214	30	0	20	0
5003	6/18	56° 00.05'	-154° 12.66'	60	4.9	958	58	557	65	0	0	0
5004	6/18	56° 00.07'	-154° 29.91'	252	4.9	168	13	121	13	34	0	15
5005	6/24	56° 00.05'	-154° 49.32'	107	5.0	194	14	159	18	20	15	0
5006	6/24	56° 00.09'	-155° 05.61'	32	5.0	70	4	220	37	0	50	0
5007	6/17	56° 09.90'	-153° 35.94'	83	5.0	478	36	524	64	0	0	0
5008	6/19	56° 10.07'	-153° 53.31'	122	4.8	1,031	67	347	38	5	5	0
5009	6/19	56° 10.23'	-154° 10.82'	64	5.0	240	15	246	37	0	0	0
5010	6/23	56° 10.19'	-154° 29.15'	41	5.1	184	13	678	99	0	0	0
5011	6/23	56° 10.12'	-154° 46.36'	41	5.0	50	3	160	28	0	5	0
5013	6/24	56° 09.47'	-155° 22.09'	18	5.1	121	8	117	17	0	0	0
5014	6/25	56° 10.33'	-155° 40.12'	34	5.0	138	7	227	37	0	0	0
5015	6/19	56° 19.51'	-153° 51.22'	49	5.0	446	22	434	62	0	0	0
5016	6/19	56° 19.87'	-154° 10.01'	50	4.9	230	13	233	32	0	29	0
5017	6/23	56° 19.58'	-154° 28.02'	38	5.0	385	23	252	33	0	69	0
5018	6/25	56° 19.94'	-155° 22.55'	27	4.9	72	4	125	20	0	0	0
5019	6/25	56° 19.73'	-155° 39.94'	39	5.0	11	1	182	35	0	25	0
5020	6/26	56° 30.40'	-155° 20.45'	31	5.0	70	4	39	7	0	20	0
5021	6/27	56° 30.49'	-155° 39.03'	70	5.0	55	4	238	33	0	40	0
5022	6/26	56° 39.66'	-155° 02.61'	23	5.0	543	16	51	7	0	15	0
5023	6/26	56° 39.97'	-155° 19.49'	46	5.0	68	4	205	30	0	20	0
5024	6/27	56° 39.69'	-155° 38.04'	130	5.0	123	8	143	17	0	10	0
5025	6/27	56° 40.00'	-155° 55.53'	160	5.0	80	5	108	14	15	0	0
5026	7/6	56° 50.06'	-154° 24.62'	33	5.0	962	41	176	24	0	5	0
5027	7/6	56° 50.23'	-154° 42.01'	29	4.9	207	9	103	18	0	5	0
5028	7/5	56° 50.03'	-155° 00.34'	41	5.0	393	19	405	58	0	10	0
5029	7/5	56° 50.32'	-155° 18.92'	123	5.0	145	9	106	14	10	0	0
5030	6/28	56° 50.02'	-155° 37.65'	155	5.0	221	13	79	10	5	0	0
5031	6/28	56° 50.02'	-155° 54.58'	166	5.0	459	28	244	29	10	0	0
5032	7/6	56° 59.90'	-154° 40.99'	23	5.1	299	12	81	14	0	0	0
5033	7/5	57° 00.05'	-154° 59.69'	67	5.0	82	6	152	22	0	0	0
5034	7/5	56° 59.64'	-155° 17.97'	137	4.9	139	8	85	10	5	0	0
5035	7/3	57° 00.09'	-155° 35.53'	152	5.0	57	4	62	8	5	0	0
5036	6/28	56° 59.57'	-155° 53.85'	167	5.0	677	45	284	35	0	0	0
5037	7/4	57° 10.06'	-154° 40.11'	33	5.0	467	20	203	29	0	0	0
5038	7/4	57° 10.34'	-154° 58.02'	107	5.0	77	6	67	8	0	0	0
5039	7/3	57° 10.02'	-155° 16.56'	135	5.0	90	6	17	2	0	0	0
5040	7/3	57° 09.95'	-155° 34.70'	147	5.1	65	4	89	11	0	0	0
5041	7/2	57° 10.34'	-155° 53.53'	144	5.1	298	15	232	26	5	5	0
5042	7/4	57° 19.77'	-154° 57.08'	104	5.0	192	14	208	26	0	30	0
5043	7/1	57° 20.03'	-155° 15.67'	136	5.0	119	7	103	12	10	0	0
5044	7/1	57° 20.00'	-155° 33.11'	154	4.9	60	3	65	7	5	0	0
5045	7/2	57° 19.74'	-155° 52.03'	55	5.0	243	16	282	38	0	5	0
5046	7/2	57° 19.79'	-156° 10.49'	137	5.0	365	20	218	28	0	15	0
5047	7/1	57° 29.80'	-155° 14.62'	142	5.1	90	5	144	18	15	0	0
5048	7/1	57° 29.89'	-155° 32.19'	165	5.0	213	12	185	23	0	0	0
5096	6/30	54° 50.04'	-157° 33.51'	219	5.0	38	3	27	3	40	0	0
5097	7/1	54° 50.01'	-157° 50.25'	88	5.0	96	7	79	10	15	15	0
5098	6/30	55° 00.01'	-157° 15.24'	104	5.0	92	6	15	2	40	15	0

¹ Standard skate =1,800' groundline with 16/0 circle hooks spaced every 18' on 24"-42" gangions.

² Weights are calculated from length-weight tables.

³ Bycatch numbers extrapolated from 20% subsample.

Regulatory Area 3B

Station	Date Fished	North Latitude	West Longitude	Depth (F)	Skates ¹	O32 Halibut		U32 Halibut Bycatch (numbers) ³				
						Lbs. ²	#'s	Lbs. ²	#'s	Sablefish	P. Cod	Rockfish
5099	6/30	55° 00.01'	-157° 32.12'	54	5.0	67	5	28	4	0	59	5
5100	7/1	54° 59.99'	-157° 50.05'	44	5.0	1,325	70	308	37	0	5	5
5101	7/1	55° 00.01'	-158° 06.94'	72	5.0	176	13	396	55	0	10	0
5102	6/28	55° 09.99'	-156° 22.26'	280	5.0	65	4	0	0	45	0	0
5103	6/28	55° 10.05'	-156° 39.01'	289	5.0	43	3	20	2	45	0	0
5104	6/29	55° 10.01'	-156° 57.23'	85	5.0	286	20	231	27	20	30	0
5105	6/29	55° 09.99'	-157° 13.95'	61	5.0	379	23	390	51	5	74	0
5106	7/8	55° 09.94'	-157° 31.56'	46	5.0	2,476	121	314	42	0	10	0
5107	7/2	55° 10.01'	-157° 49.00'	43	5.0	842	41	187	24	0	0	0
5108	7/2	55° 10.00'	-158° 07.04'	55	5.0	383	25	493	68	0	15	0
5109	6/28	55° 20.03'	-156° 38.81'	66	5.0	356	23	290	36	0	200	0
5110	6/29	55° 20.11'	-156° 55.98'	51	5.0	541	33	429	57	0	10	5
5111	7/8	55° 20.19'	-157° 14.32'	48	5.0	693	45	417	57	0	25	0
5112	7/8	55° 19.99'	-157° 30.76'	47	5.0	799	40	282	40	0	5	0
5113	7/2	55° 19.75'	-157° 48.92'	44	4.9	292	13	321	49	0	10	0
5114	7/3	55° 20.00'	-158° 06.05'	58	4.9	140	9	300	43	0	64	0
5115	7/3	55° 20.03'	-158° 24.03'	80	4.9	13	1	288	40	5	15	0
5117	7/9	55° 30.05'	-156° 55.08'	48	5.0	1,066	53	269	32	0	0	10
5118	7/10	55° 29.97'	-157° 13.49'	47	5.0	686	41	481	69	0	10	0
5119	7/10	55° 29.84'	-157° 30.73'	51	5.0	171	8	517	72	0	54	0
5120	7/11	55° 29.91'	-157° 48.22'	51	5.0	224	16	316	44	0	59	0
5121	7/7	55° 30.01'	-158° 05.97'	70	5.0	45	3	214	32	10	45	0
5122	7/3	55° 30.01'	-158° 23.99'	79	5.0	215	14	224	30	0	64	0
5123	7/9	55° 40.10'	-156° 55.22'	48	5.0	646	35	545	79	0	54	0
5124	7/10	55° 40.05'	-157° 12.52'	47	5.0	347	16	439	67	0	20	0
5125	7/11	55° 39.91'	-157° 30.48'	54	5.0	224	13	273	41	0	84	0
5126	7/11	55° 40.16'	-157° 48.10'	72	4.9	154	10	252	37	10	39	0
5127	7/12	55° 39.79'	-158° 06.62'	70	4.9	142	9	200	29	29	24	0
5128	7/4	55° 39.99'	-158° 23.05'	71	5.0	89	6	159	25	0	20	0
5129	7/4	55° 40.03'	-158° 41.12'	49	4.9	437	23	412	65	0	83	0
5130	7/13	55° 50.09'	-157° 11.80'	56	4.9	101	7	274	43	0	103	0
5131	7/13	55° 50.08'	-157° 29.66'	55	5.0	118	7	101	16	0	75	0
5132	7/12	55° 50.01'	-157° 47.47'	67	4.9	83	6	199	27	20	15	0
5133	7/12	55° 50.02'	-158° 04.42'	44	4.9	461	25	489	79	0	64	0
5134	7/4	55° 50.03'	-158° 23.13'	59	5.0	372	21	208	30	0	15	0
5135	7/13	56° 00.05'	-157° 29.15'	65	5.0	12	1	234	36	0	119	0
5136	6/4	55° 59.98'	-157° 47.07'	68	5.0	138	8	158	24	0	5	0
5137	6/4	55° 59.93'	-158° 04.94'	47	5.0	195	7	44	7	0	25	0
5138	6/3	56° 10.12'	-157° 46.97'	86	5.0	495	17	40	6	0	20	0
5139	6/3	56° 10.19'	-158° 04.96'	43	5.0	533	18	47	9	0	35	0
5140	6/3	56° 20.05'	-158° 03.98'	34	5.0	394	14	9	2	0	50	0
5141	6/19	54° 29.90'	-159° 00.51'	172	5.0	147	9	54	6	15	0	10
5142	6/19	54° 29.95'	-159° 17.02'	80	5.0	152	11	329	45	0	59	0
5143	6/18	54° 29.91'	-159° 33.97'	62	4.9	508	32	423	53	0	88	5
5144	6/17	54° 30.01'	-159° 51.17'	65	5.0	139	10	312	45	0	40	0
5145	6/17	54° 30.09'	-160° 09.03'	66	4.9	146	9	322	46	0	83	0
5146	6/21	54° 39.97'	-158° 24.98'	117	5.0	560	36	166	19	30	15	0
5147	6/20	54° 39.93'	-158° 41.99'	57	5.0	633	37	446	58	0	50	10
5148	6/19	54° 40.07'	-159° 00.22'	50	5.0	713	37	262	34	0	10	0
5149	6/18	54° 40.05'	-159° 17.02'	40	5.0	693	31	195	28	0	5	0

¹ Standard skate = 1,800' groundline with 16/0 circle hooks spaced every 18' on 24"-42" gangions.

² Weights are calculated from length-weight tables.

³ Bycatch numbers extrapolated from 20% subsample.

Regulatory Area 3B

Station	Date Fished	North Latitude	West Longitude	Depth (F)	Skates ¹	O32 Halibut		U32 Halibut Bycatch (numbers) ³				
						Lbs. ²	#'s	Lbs. ²	#'s	Sablefish	P. Cod	Rockfish
5150	6/18	54° 40.01'	-159° 34.16'	35	5.0	659	23	110	18	0	10	15
5151	6/16	54° 40.08'	-159° 52.23'	42	4.9	1,226	42	221	33	0	10	0
5152	6/17	54° 40.01'	-160° 09.17'	49	5.0	303	13	454	62	0	90	0
5153	6/21	54° 50.01'	-158° 06.99'	54	5.0	513	35	310	41	0	20	0
5154	6/21	54° 49.95'	-158° 25.05'	109	5.0	278	18	99	13	15	0	0
5155	6/20	54° 49.91'	-158° 42.03'	54	5.0	475	26	331	44	0	25	0
5156	6/20	54° 50.08'	-159° 00.09'	39	5.0	239	12	273	40	0	99	0
5157	6/16	54° 50.00'	-159° 52.12'	30	5.0	303	11	86	15	0	50	0
5158	6/16	54° 50.01'	-160° 08.98'	38	5.0	86	4	74	16	0	15	0
5159	6/15	54° 49.95'	-160° 26.54'	47	5.0	30	2	226	34	0	119	0
5160	6/22	54° 59.88'	-158° 25.01'	114	5.0	645	38	123	14	5	10	0
5161	6/22	54° 59.95'	-158° 42.06'	69	5.0	80	5	260	39	0	50	0
5162	6/10	54° 59.90'	-158° 59.07'	46	5.0	94	4	143	28	0	89	0
5163	6/10	55° 00.00'	-159° 16.97'	22	5.0	1,951	50	29	3	0	0	0
5164	6/15	55° 00.03'	-160° 26.99'	63	5.0	146	8	303	40	5	65	0
5165	6/15	54° 59.93'	-160° 44.01'	47	5.0	261	13	219	33	0	20	0
5166	6/8	55° 09.97'	-158° 24.01'	101	5.0	100	6	54	7	5	0	0
5167	6/8	55° 10.03'	-158° 41.87'	112	5.0	368	21	190	22	10	10	0
5168	6/10	55° 09.88'	-158° 58.99'	76	5.0	184	12	256	38	0	40	0
5169	6/11	55° 10.00'	-159° 17.03'	38	5.0	484	19	107	16	0	5	0
5170	6/8	55° 20.02'	-158° 42.17'	100	5.0	321	16	112	13	0	0	0
5171	6/9	55° 20.05'	-158° 59.15'	102	5.0	255	13	27	3	0	0	0
5172	6/9	55° 20.02'	-159° 17.00'	97	5.0	280	17	168	21	0	5	0
5173	6/11	55° 20.03'	-159° 34.07'	76	5.0	282	16	270	37	0	15	5
5174	6/12	55° 20.03'	-159° 51.98'	46	5.0	188	5	109	16	0	45	0
5175	6/7	55° 29.91'	-158° 41.01'	87	5.0	485	28	166	21	10	0	0
5176	6/7	55° 29.90'	-158° 58.94'	60	5.0	244	14	401	58	0	0	0
5177	6/9	55° 30.01'	-159° 17.31'	66	5.0	224	16	332	46	0	25	0
5178	6/11	55° 30.08'	-159° 34.25'	92	5.0	354	18	291	35	0	35	0
5179	6/12	55° 29.98'	-159° 52.01'	92	5.0	358	18	236	31	0	40	0
5181	6/7	55° 39.87'	-158° 59.00'	83	5.0	658	32	327	46	0	35	0
5182	6/6	55° 39.96'	-159° 17.06'	57	5.0	342	14	130	19	0	20	0
5183	6/12	55° 40.01'	-159° 52.00'	71	5.0	473	22	64	9	0	99	0
5184	6/6	55° 49.89'	-158° 58.97'	69	5.0	676	28	57	8	0	50	0
5185	6/6	55° 49.98'	-159° 17.05'	29	5.0	429	12	16	3	0	25	0
5186	6/22	54° 00.01'	-163° 15.20'	46	5.0	118	8	349	52	0	223	0
5187	6/22	54° 00.01'	-163° 32.43'	54	5.0	27	2	278	48	0	70	0
5188	6/22	54° 00.05'	-163° 49.01'	51	5.0	57	3	246	40	0	69	0
5189	6/10	54° 09.99'	-161° 34.03'	74	5.0	144	11	300	43	0	35	0
5190	6/10	54° 10.01'	-161° 51.00'	45	5.0	437	25	534	71	0	25	15
5191	6/11	54° 10.02'	-162° 08.19'	47	5.0	153	10	216	32	0	69	10
5192	6/11	54° 09.99'	-162° 25.34'	91	5.0	0	0	40	5	5	110	0
5193	6/22	54° 10.29'	-163° 49.98'	49	5.0	47	4	293	48	0	59	0
5194	6/7	54° 19.99'	-160° 08.12'	177	5.0	40	3	124	16	20	0	10
5195	6/7	54° 20.00'	-160° 26.05'	69	5.0	198	13	466	64	0	114	0
5196	6/9	54° 19.91'	-160° 43.02'	58	5.0	309	23	468	62	0	74	0
5197	6/9	54° 20.03'	-161° 00.00'	71	5.0	170	12	709	96	5	70	0
5198	6/13	54° 20.01'	-161° 17.20'	59	5.0	368	22	557	77	0	54	0
5199	6/10	54° 19.99'	-161° 33.88'	80	5.0	124	9	312	40	10	50	5
5200	6/10	54° 19.99'	-161° 50.64'	40	5.0	322	14	383	55	0	144	0

¹ Standard skate = 1,800' groundline with 16/0 circle hooks spaced every 18' on 24"-42" gangions.

² Weights are calculated from length-weight tables.

³ Bycatch numbers extrapolated from 20% subsample.

2017 IPHC Fishery-Independent Setline Survey

Regulatory Area 3B

Station	Date Fished	North Latitude	West Longitude	Depth (F)	Skates ¹	O32 Halibut		U32 Halibut Bycatch (numbers) ³				
						Lbs. ²	#'s	Lbs. ²	#'s	Sablefish	P. Cod	Rockfish
5201	6/11	54° 20.00'	-162° 09.02'	32	5.0	902	33	206	38	0	0	0
5202	6/21	54° 19.75'	-163° 17.04'	27	5.0	296	14	122	18	0	10	0
5203	6/21	54° 20.10'	-163° 34.00'	60	5.0	82	3	278	46	5	60	0
5204	6/23	54° 19.99'	-163° 51.10'	62	5.0	136	7	263	43	0	100	0
5205	6/23	54° 20.00'	-164° 08.70'	50	5.0	21	1	167	35	0	94	0
5206	6/7	54° 29.93'	-160° 26.02'	81	5.0	137	10	292	42	5	54	0
5207	6/9	54° 30.00'	-160° 42.99'	77	5.0	129	9	209	32	10	35	0
5208	6/9	54° 29.99'	-160° 59.90'	72	5.0	148	7	226	37	10	15	0
5209	6/13	54° 29.89'	-161° 18.01'	66	5.0	115	5	250	37	15	65	0
5210	6/13	54° 30.04'	-161° 34.98'	36	5.0	525	25	454	73	0	0	0
5211	6/12	54° 30.02'	-161° 52.14'	77	5.0	209	13	326	44	10	10	0
5212	6/12	54° 30.01'	-162° 09.16'	78	5.0	339	22	253	34	0	30	0
5213	6/12	54° 30.01'	-162° 26.08'	81	5.0	309	18	273	36	0	25	5
5214	6/21	54° 29.85'	-163° 17.79'	38	5.0	254	15	348	51	0	69	0
5215	6/21	54° 30.00'	-163° 34.78'	52	5.0	128	8	199	34	0	5	0
5216	6/23	54° 30.00'	-163° 52.99'	52	5.0	187	8	304	50	0	35	0
5217	6/23	54° 30.00'	-164° 09.88'	51	5.0	36	3	353	57	0	30	0
5218	6/7	54° 39.96'	-160° 26.21'	55	5.0	138	8	529	83	0	35	0
5219	6/8	54° 40.01'	-160° 43.11'	52	5.0	248	13	349	61	0	30	0
5220	6/8	54° 39.90'	-161° 00.99'	51	5.0	127	6	236	41	0	15	0
5221	6/14	54° 39.96'	-161° 18.01'	76	5.0	167	11	297	44	0	45	0
5222	6/13	54° 40.07'	-161° 34.99'	37	5.0	365	15	273	41	0	5	5
5223	6/12	54° 40.05'	-161° 53.02'	30	5.0	381	13	266	41	0	0	0
5224	6/20	54° 40.00'	-162° 43.51'	47	4.9	39	2	110	19	0	39	0
5225	6/8	54° 50.00'	-160° 44.07'	56	5.0	110	5	248	38	0	35	0
5226	6/8	54° 49.99'	-161° 00.99'	57	5.0	38	3	213	36	0	15	0
5227	6/14	54° 49.95'	-161° 18.02'	57	5.0	94	6	352	51	0	30	0
5228	6/14	54° 49.98'	-161° 35.90'	46	5.0	1,085	29	182	29	0	0	0
5229	6/20	54° 49.91'	-162° 44.99'	30	5.0	468	14	131	22	0	25	0
5230	6/20	54° 50.01'	-163° 02.77'	45	5.0	693	35	301	40	0	74	0
5231	6/15	55° 00.00'	-161° 01.01'	51	5.0	368	15	362	52	0	25	0
5232	6/14	55° 00.02'	-161° 19.10'	47	5.0	978	28	225	33	0	25	0
5233	6/15	55° 10.01'	-161° 02.14'	64	5.0	470	17	125	18	0	140	0
5234	6/8	55° 19.82'	-156° 02.80'	153	5.0	1,184	78	509	58	41	9	6
5235	6/8	55° 19.92'	-156° 20.88'	94	5.0	138	10	168	20	44	12	0
5236	6/2	55° 29.86'	-155° 44.38'	120	5.0	95	6	140	17	14	39	9
5237	6/2	55° 29.82'	-156° 02.78'	111	5.0	167	11	90	12	27	30	1
5238	6/8	55° 30.14'	-156° 19.82'	120	5.0	751	51	336	40	46	9	0
5239	6/1	55° 40.06'	-155° 25.84'	102	4.3	97	8	152	22	6	71	2
5240	6/2	55° 39.89'	-155° 43.67'	71	5.0	462	24	463	63	0	79	0
5241	6/3	55° 39.74'	-156° 01.77'	126	5.0	112	8	157	19	60	8	2
5242	6/3	55° 39.73'	-156° 18.78'	139	5.0	436	27	200	23	37	0	1
5243	6/9	55° 39.71'	-156° 36.80'	131	5.0	617	43	342	40	34	1	1
5244	6/1	55° 49.89'	-155° 06.68'	66	5.0	333	24	820	113	0	4	0
5245	6/1	55° 49.83'	-155° 24.76'	26	5.0	95	4	11	2	0	0	0
5246	6/11	55° 49.74'	-156° 01.14'	60	5.0	476	32	660	87	0	24	0
5247	6/3	55° 49.78'	-156° 18.78'	132	5.0	206	14	197	26	48	1	0
5248	6/9	55° 49.66'	-156° 35.77'	125	5.0	333	24	584	72	27	6	0
5249	6/9	55° 49.89'	-156° 53.87'	74	4.9	162	12	430	58	4	63	0
5250	6/11	55° 59.74'	-155° 42.11'	26	5.0	14	1	167	28	0	39	0

¹ Standard skate = 1,800' groundline with 16/0 circle hooks spaced every 18' on 24"-42" gangions.

² Weights are calculated from length-weight tables.

³ Bycatch numbers extrapolated from 20% subsample.

2017 IPHC Fishery-Independent Setline Survey Regulatory Area 3B

Station	Date Fished	North Latitude	West Longitude	Depth (F)	Skates ¹	O32 Halibut		U32 Halibut Bycatch (numbers) ³				
						Lbs. ²	#'s	Lbs. ²	#'s	Sablefish	P. Cod	Rockfish
5251	6/11	55° 59.68'	-156° 00.17'	41	5.0	183	12	511	80	0	25	0
5252	6/7	55° 59.85'	-156° 18.05'	116	5.0	515	33	303	38	4	47	0
5253	6/7	55° 59.39'	-156° 34.81'	107	5.0	353	20	311	42	2	55	3
5254	6/12	55° 59.92'	-157° 10.43'	63	5.0	96	6	431	66	0	34	0
5255	6/16	56° 09.62'	-155° 59.24'	121	5.0	499	31	600	73	0	78	0
5256	6/7	56° 09.94'	-156° 16.84'	128	4.9	543	37	573	69	24	13	0
5257	6/7	56° 09.89'	-156° 34.87'	103	5.0	76	5	195	29	0	22	0
5258	6/17	56° 09.76'	-156° 53.07'	45	5.0	176	8	93	16	0	8	0
5259	6/12	56° 09.80'	-157° 10.78'	55	5.0	201	9	285	46	0	90	0
5260	6/12	56° 09.82'	-157° 28.78'	85	5.0	251	14	190	23	0	13	0
5261	6/16	56° 19.77'	-155° 57.77'	115	5.0	101	7	126	17	0	3	0
5262	6/16	56° 19.78'	-156° 15.86'	156	5.0	56	3	36	4	6	1	1
5263	6/16	56° 19.76'	-156° 34.19'	100	5.0	418	28	510	61	0	20	1
5264	6/17	56° 19.89'	-156° 51.47'	65	5.0	368	21	494	73	0	18	0
5265	6/17	56° 20.51'	-157° 10.06'	94	5.0	689	43	147	20	0	24	0
5266	6/13	56° 19.86'	-157° 27.73'	36	5.0	765	27	224	34	0	1	6
5267	6/13	56° 19.78'	-157° 46.09'	29	5.0	756	22	91	14	0	31	0
5268	6/18	56° 29.80'	-155° 56.78'	135	5.0	26	2	80	10	1	2	0
5269	6/18	56° 29.89'	-156° 14.44'	142	5.0	121	8	139	18	6	6	0
5270	6/19	56° 29.89'	-156° 32.78'	106	5.0	216	15	287	37	0	6	0
5271	6/19	56° 29.68'	-156° 51.41'	54	5.0	164	11	400	65	0	28	0
5272	6/13	56° 29.79'	-157° 27.77'	81	5.0	324	17	232	28	0	16	0
5273	6/18	56° 39.80'	-156° 13.75'	117	5.0	173	12	254	34	1	4	1
5274	6/19	56° 39.67'	-156° 32.28'	84	5.0	836	44	484	62	0	10	0
5275	6/20	56° 39.80'	-156° 50.75'	55	5.0	127	9	419	57	0	11	0
5276	6/20	56° 39.72'	-157° 08.73'	85	5.0	236	15	157	21	0	13	0
5277	6/21	56° 49.80'	-156° 12.69'	104	5.0	881	48	350	45	0	11	1
5278	6/21	56° 49.80'	-156° 31.70'	63	4.9	629	30	497	68	0	22	0
5279	6/20	56° 49.77'	-156° 49.80'	64	5.0	174	12	513	68	0	27	0
5280	6/21	56° 59.77'	-156° 12.80'	86	4.9	453	27	269	36	0	34	0
230 Total Effective 3B Stations					Totals	75,141	3,983	58,386	8,178	1,047	6,911	174

¹ Standard skate =1,800' groundline with 16/0 circle hooks spaced every 18' on 24"-42" gangions.

² Weights are calculated from length-weight tables.

³ Bycatch numbers extrapolated from 20% subsample.